

ENGINE	SINGLE CYLINDER - 4 STROKE - SINGLE OVER HEAD CAM AND 2 VALVES
DISPLACEMENT	200 CM ³
BORE X STROKE	65.5 X 59.3 MM
COMPRESSION RATIO	9.25 ± 0.5 : 1
MAXIMUM OUTPUT POWER	8.6 KW A 6500 RPM
MAXIMUM TORQUE	15 NM A 4250 RPM
LUBRICATION	OIL IN CARTER
IGNITION SYSTEM	ELECTRONIC (CDI)
START-UP	ELECTRIC AND KICK START
MUFFLER	CATALYST WITH SECONDARY AIR INJECTION
GEAR	MANUAL 4 SPEED
SEAT HEIGHT	820 MM
DIMENSIONS (L X W X H)	1760 X 695 X 1110 MM
WHEEL BASE	1235 MM
FRONT SUSPENSION	SWING-ARM, HELICAL SPRING AND HYDRAULIC DAMPERS DOUBLE EFFECT
REAR SUSPENSION	ENGINE AS SWING-ARM AND HYDRAULIC DAMPERS DOUBLE EFFECT
WHEEL RIM	MODULAR PRESSED STEEL
TYRES FRONT-REAR	3.5 - 10
FRONT BRAKE	INOX STEEL DISC Ø 200 MM
REAR BRAKE	DRUM 150 MM
FRAME	MIXED STRUCTURE WITH CHASSIS AND TUBES IN STEEL
WEIGHT	118 KG